

HS-CC719F

1/3-Inch CCD Dome Camera



Camera

Feature

- For Use With 1/3" Format Camera
- With 0.5 Lux Low Light Sensitivity
- With 380 TV Lines Horizontal Resolution
- Auto Electronic Shutter Up To 1/60(1/50) ~1/100,000 Second
- Compact, Solid-state Body In Lightness



Specification

Model	HS-CC719F
General	
Pick up device	1/3" interline transfer CCD
Total Pixels	NTSC:537(H) x 505(V) / PAL:537(H) x 597(V)
Effective Pixels	NTSC:510(H) x 492(V) / PAL:500(H) x 582(V)
Resolution	With 380 TV lines
Sync. System	Internal Sync.
Scanning System	NTSC: 525 Lines / 60 Fields ; PAL: 625 Lines / 50 Fields
S/N Ratio	More than 48 dB
Electronic Shutter	Auto/manual 1/60 (1/50) ~1/100,000 sec.
Gamma Correct	0.45 / 1 (set to 0.45 before shipment)
Min. Illumination	0.5 lux / F1.2
Video Output	Composite 1.0 Vp-p / 75 ohm
Frequency	
Horizontal	NTSC: 15.734 KHz ; PAL: 15.625 KHz
Vertical	NTSC: 60 Hz ; PAL: 50 Hz
Backlight Compensation	on/off switchable
Lens Mount Type	
Lens Type	Board lens 3.6mm, 6mm, 8mm
Electrical	
DC power Source	DC12V
Power Consumption	2W (Max)
Current	200mA (Max)
Weight	N.W./G.W.: 0.125kg / 0.185kg
Dimension	107(Diameter) x 65(H)mm
Operation Temperature	-10 to 50 °C (14 to 122 °F)
Storage Temperature	-20 to 70 °C (-4 to 158 °F)

Dimension

