



HS-CC756

1/3-Inch D.S.P Color CCD Camera

Feature

- For use with 1/3" format camera
- With 0.05 low light sensitivity
- With 480 TV lines horizontal resolution
- Auto electronic shutter up to 1/60(1/50) ~1/10,000 second
- Accepts C & Cs mount with precision double cam
- Compact, solid-state body in lightness



Specification

Model	HS-CC756
General	
Pick up device	1/3" interline transfer CCD
Total Pixels	NTSC: 811(H) x 508(V) / PAL: 795(H) x 596(V)
Effective Pixels	NTSC: 768 (H) x 494(V) / PAL:752 (H) x 582 (V)
Resolution	480 TV lines
Sync. System	Internal Sync / Line Lock(DIP button control).
Scanning System	NTSC: 525 Lines / 60 Fields PAL: 625 Lines / 50 Fields
S/N Ratio	More than 50 dB
Electronic Shutter	Auto/manual 1/60 (1/50) ~1/10,000 sec.
Gamma Correct	0.45
Min. Illumination	0.05 lux / F1.2
Video Output	Composite 1.0 Vp-p / 75 ohm
Audio Output	0.8V (10 k ohm)
Filk	ON/OFF Switch
Gain Control	AGC/S AGC (11/8 Lux turn B/W)
White Balance	Auto/ Manual
Day & Night	ON/OFF(D/N by motor LQFP change)
Frequency	
Horizontal	NTSC: 15.734 KHz ; PAL: 15.625 KHz
Vertical	NTSC: 49.94 Hz ; PAL: 50 Hz
Backlight Compensation	on/off switchable
Lens Mount Type	
Lens Drive	Optional DC / Video drive
Electrical	
DC power Source	DC12V / AC24V , 90~260V AC option
Power Consumption	3.4 W
Current	280mA (Max) / DC12V
Weight (per unit)	N.W./G.W.: 490g / 790g
Dimension	63.9(W) x 133.4(D) x 64.0(H)mm
Operation Temperature	-10 to 50 °C (14 to 122 °F)
Storage Temperature	-20 to 70 °C (-4 to 158 °F)

Dimension

