

## 4CH / 8CH / 16CH Dual Stream Standalone DVR

**HS-DM4060**  
**HS-DM8030**  
**HS-DM6030**

### Feature

- Multi Functional: Record / Playback / Backup / Internet
- DUAL Stream, M-JPEG Recording & MPEG-4 Transmitting over Internet
- ENHANCED "Picture Quality"
- FASTER "Internet Transmitting"
- "AUDIO" included when Remote Backup / USB Backup(AVI file export)
- IE Brower Supported
- Completed TCP/IP / PPPoE / DHCP / DDNS Networking Supported
- Frame Rate Adjustable under Each Mode per Channel
- Max. 4 HDD (16 CH) x 750G Supported. HDD Readable in PC
- DVR and PTZ control (Keypad / Remote controller / Network / Mouse)
- English / Chinese / Multi Languages supported
- Alarm / Motion screen popup
- Auto record function




### Specification


Model	HS-DM4060	HS-DM8030	HS-DM6030
System	NTSC / PAL / Auto		
Input	4 / 8 / 16CH input 1.0Vp-p, 75ohm unbalanced (BNC type)		
Output	Main monitor x 1 / VGA (optional)	Main / call monitor x 1 / VGA x 1	
S/N Ratio	More than 40dB		
Color	16.7 million		
<b>Monitoring Method</b>			
Display Channel	1 / 4	1 / 4 / 9	1 / 4 / 9 / 16
Sequence Display	Available		
Display Resolution	NTSC:640(H) x 448(V) ; PAL :640(H) x 544(V)		NTSC : 704(H) x 448(V) PAL : 704(H) x 544(V)
Display Rate	120 fps (NTSC) / 100fps (PAL)	240 fps (NTSC) / 200fps (PAL)	480 fps (NTSC) / 400fps (PAL)
<b>Recording / Play Function</b>			
Recording Resolution	NTSC:640 x 224 ; PAL :640 x 272		NTSC:704 x 224 ; PAL :704 x 272 NTSC:352 x 224 ; PAL :352 x 272
Recording Rate	NTSC: Max 60~0 fps PAL: Max 50~0 fps		704 x 224 : Max 60~0 fps(NTSC) 704 x 272 : Max 50~0 fps(PAL) 352 x 224 : Max 120~0 fps(NTSC) 352 x 272 : Max 100~0 fps(PAL)
Record Quality	High/ Normal / Low		
Compression Method	Storage: M-JPEG, network / internet: MPEG-4		
Recording Mode	Auto / manual / schedule / motion / alarm		
Playback Mode	Time list / Event list / Date & Time search		
<b>Other Function</b>			
Operation	Record / Play / Network / Backup		
Motion Detect	16 x 16 grids camera for all channel		
Alarm Function	4 input / 1 output	8 input / 1 output	16 input / 1 output
Backup	USB 1.1/2.0 / Network remote backup		
Storage	HDD x 2		HDD x 4
Audio Input	RCA x1		RCA x4
Audio Output	RCA x1		RCA x2
HDD Record Mode	Full stop / overwrite		
PTZ Control	PELCO-D, PELCO-P, MERIT LI-LIN		
Key Lock	Yes		
Real Time Clock (RTC)	Support NTP (Network Time Protocol), Daylight Saving Time		
Remote Control	Optional		
<b>Network Function</b>			
Ethernet	10/100 Base-T		
Web Interface	Support licensed software AP / IE		
Network Connection	TCP/IP, PPPoE, DHCP, DDNS		
Client Application	Display / playback / DVR control / PTZ Control		
<b>Mechanical</b>			
Power Supply	DC 12V / 5A		
Weight	N.W./G.W.: 3.06kg / 3.68kg		
Dimension	426(W) x 328.5(D) x 65(H)mm		
Operating Temperature	5°C~+40°C (41°F~104°F)		
Operating Humidity	Less than 90%		
Certification	CE / FCC		

### Dimension

HS-DM4060



HS-DM8030



HS-DM6030

