

Outdoor Star-Light Camera

CCD CAMERA

TC32LF-1

1/3" COLOR CCD CAMERA(MID-RES)

TC34LF-1

1/3" COLOR CCD CAMERA(HI-RES)

NEW PRODUCT!!

SONY SENSOR INSIDE



Standard Camera

IR Camera

Star Light Camera



FEATURE

- 24-hour operational camera with perfect picture performance.
- Unique looks for outdoor
- Packing camera, lens, bracket as a set.
- Water resistant of aluminum die-cast pass IP 66 test.
- Easy to install.
- Anti-Thunder circuit prevents tube struck by thunder.
- Sensitivity is higher than the general cameras
- Color fidelity at day and night (or dark view)



Model	TC32LF-1(MID-RES)	TC34LF-1(HI-RES)
Image device	1/3" color CCD sensor interline	
Effective picture elements	NTSC 510(H) x 492(V) PAL 500(H) x 582(V)	NTSC 768(H) x 494(V) PAL 752(H) x 582(V)
Scanning system	2:1 interlace	
Synchronizing system	Internal	
Horizontal resolution	More than 420 TV lines	More than 480 TV lines
Electronic shutter control	Auto-Electronic Shutter (1/60~1/100000 sec)NTSC; (1/50~1/100000 sec)PAL	
Gamma	0.45	
Minimum illumination	0.001 Lux/F1.0	0.005 Lux/F1.0
Video output level	1Vp-p / 75Ω	
Video S/N ratio	50 dB (AGC off)	
White balance	Auto (2500°K~9500°K)	
Backlight compensation	Yes	
Storage temperature	-30°C~80°C	
Operating temperature	-10°C~50°C	
Power requirements	DC 12V±10%	
Power consumption(DC12V)	210mA	
Dimensions	83 (L)X90(W)X160(H) mm	
Weight	650g	
Lens Standard	STD: 4.0 /6.0mm / 8.0mm /F1.1 Option: 12.0mm/16.0mm	